



Bridge Design - Loads and Load Combinations

Course Number: CE-02-401

PDH: 4

Approved for: AK, AL, AR, FL, GA, IA, IL, IN, KS, KY, LA, MD, ME, MI, MN, MO, MS, MT, NC, ND, NE, NH, NJ, NM, NV, NY, OH, OK, OR, PA, SC, SD, TN, TX, UT, VA, VT, WI, WV, and WY

State Board Approvals

Florida Provider # 0009553 License #868

Indiana Continuing Education Provider #CE21800088

Maryland Approved Provider of Continuing Professional Competency

New Jersey Professional Competency Approval #24GP00025600

North Carolina Approved Sponsor #S-0695

NYSED Sponsor #274

Course Author: Mathew Holstrom

How Our Written Courses Work

This document is the course text. You may review this material at your leisure before or after you purchase the course.

After the course has been purchased, review the technical material and then complete the quiz at your convenience.

A Certificate of Completion is available once you pass the exam (70% or greater).

If a passing grade is not obtained, you may take the quiz as many times as necessary until a passing grade is obtained).

If you have any questions or technical difficulties, please call (508) 298-4787 or email us at admin@PDH Pro.com.





TABLE OF CONTENTS

1.	INTRODUCTION	3
1.1.1	Load Path.....	3
1.2	LOAD DEFINITIONS	5
1.2.1	Permanent Loads	5
1.2.2	Transient Loads.....	5
1.3	PERMANENT LOAD APPLICATION WITH EXAMPLES.....	5
1.3.1	Dead Load of Components, <i>DC</i>	7
1.3.2	Dead Load of Wearing Surfaces and Utilities, <i>DW</i>	7
1.3.3	Downdrag, <i>DD</i>	8
1.3.4	Horizontal Earth Pressure, <i>EH</i>	8
1.3.5	Vertical Pressure from Dead Load of Earth Fill, <i>EV</i>	9
1.3.6	Earth Surcharge, <i>ES</i>	9
1.3.7	Force Effect Due to Creep, <i>CR</i>	9
1.3.8	Force Effect Due to Shrinkage, <i>SH</i>	9
1.3.9	Forces from Post-Tensioning, <i>PS</i>	10
1.3.10	Miscellaneous Locked-in Force Effects Resulting from the Construction Process, <i>EL</i> ..	11
1.4	TRANSIENT LOAD APPLICATION WITH EXAMPLES	11
1.4.1	Vehicular Live Load, <i>LL</i>	11
1.4.2	Vehicular Dynamic Load Allowance, <i>IM</i>	17
1.4.3	Vehicular Braking Force, <i>BR</i>	17
1.4.4	Vehicular Centrifugal Force, <i>CE</i>	18
1.4.5	Live Load Surcharge, <i>LS</i>	19
1.4.6	Pedestrian Live Load, <i>PL</i>	20
1.4.7	Uniform Temperature, <i>TU</i>	20
1.4.8	Temperature Gradient, <i>TG</i>	22
1.4.9	Settlement, <i>SE</i>	22
1.4.10	Water Load and Stream Pressure, <i>WA</i>	22
1.4.11	Wind Load on Structure, <i>WS</i>	24
1.4.12	Wind on Live Load, <i>WL</i>	26
1.4.13	Friction, <i>FR</i>	27



Bridge Design - Post-Tensioned Concrete Girders

1.4.14	Ice Load, <i>IC</i>	28
1.4.15	Vehicular Collision Force, <i>CT</i>	28
1.4.16	Vessel Collision Force, <i>CV</i>	29
1.4.17	Earthquake, <i>EQ</i>	29
1.5	LOAD DISTRIBUTION FOR BEAM-SLAB BRIDGES.....	29
1.5.1	Permanent Loads.....	29
1.5.2	Live Loads on Superstructure.....	30
1.5.3	Live Loads on Substructure.....	38
1.5.4	Skew Modification of Shear Force in Superstructures.....	42
1.6	LOAD FACTORS AND COMBINATION.....	45
	NOTATION.....	47
	REFERENCES.....	50

1. INTRODUCTION

Properly identifying bridge loading is fundamental to the design of each component. Bridge design is iterative in the sense that member sizes are a function of loads and loads are a function of member sizes. It is, therefore, necessary to begin by proportioning members based on prior experience and then adjusting for actual loads and bridge geometry.

This course summarizes the loads to be applied to bridges specified in the *AASHTO LRFD Bridge Design Specifications*, 6th Edition (AASHTO, 2012) and the *California Amendments to the AASHTO LRFD Bridge Design Specifications* (CA) (Caltrans, 2014). It is important to realize that not every load listed will apply to every bridge. For example, a bridge located in Southern California may not need to consider ice loads. A pedestrian overcrossing structure may not have to be designed for vehicular live load.

1.1.1 Load Path

The Engineer must provide a clear load path. The following illustrates the pathway of truck loading into the various elements of a box girder bridge.




Figure 3.1-1 Truck Load Path from Deck Slab to Girders

The weight of the truck is distributed to each axle of the truck. One half of the axle load then goes to each wheel or wheel tandem. This load will be carried by the deck slab which spans between girders, see Figure 3.1-1.

Once the load has been transferred to the girders, the direction of the load path changes from transverse to longitudinal. The girders carry the load by spanning between bents and abutments (Figure 3.1-2).




Figure 3.1-2 Truck Load Path from Girders to Bents




Figure 3.1-3 Truck Load on Bent Cap

When the girder load reaches the bent caps or abutments, it once again changes direction from longitudinal to transverse. The bent cap beam transfers the load to the columns. Load distribution in the substructure is covered in Section 3.5.3. The columns are primarily axial load carrying members and carry the load to the footing and finally to the piles. The piles transfer the load to the soil where it is carried by the soil matrix.

Load distribution can be described in a more refined manner, however, the basic load path from the truck to the ground is as described above. Each load in Table CA 3.4.1-1 has a unique load path. Some are concentrated loads, others are uniform line loads, while still others, such as wind load, are pressure forces on a surface.



Purchase this course to
see the remainder of
the technical materials.